

vas. _____

oik. _____

The diagram shows a longitudinal profile of a sewer line. The vertical axis represents elevation in meters, with markers at 105, 110, and 115. The horizontal axis represents the length of the sewer line. The profile includes a solid black line for the sewer invert, a dashed blue line for the ground surface, and a shaded area representing the sewer pipe structure. Slope values are indicated at various points: 0.0174, 0.0191, 0.0219, 0.0198, and 0.0011. Manhole locations are marked with vertical lines and labels: S=500, S=500, S=2000, S=1000, and S=1000. A specific manhole is labeled KLV3 at an elevation of 113.19. The profile starts at an elevation of 110.34 and ends at 110.11.

	16.86	
-0.0011		
114.53	114.69	
114.65	114.68	301.20
300		

PÄÄLLYSTE	KiTu	5 cm	48 MN/m ²
KANTAVAKERROS	KaM 0-32	10 cm	44 MN/m ²
JAKAVAKERROS	KaM 0-56/0-9	40 cm	31 MN/m ²
SUODATINKANGAS N 3			
YHTEENSÄ		55 cm	10 MN/m ²

KiTu 184 MN/m²
 KaM 280 MN/m²
 KaM 280 MN/m²
 F 10 MN/m²

Korkeusjärjestelmä N 2000		Koordinaattijärjestelmä EUREF FIN GK24		
K.osa / kylä Siivikkala		Viranomaisen arkistointimerkintöjä varten		
Rakennustoimenpide		Piirustuslaji		
Rakennuskohteen nimi METTISTÖN KEVYENLIIKENTEEN- VÄYLÄ V: TUOMAANTIE- SIMEONINTIE (KLV2)		Piirustuksen sisältö Mittakaava PITUUSLEIKKAUS 1:100/1:1000		
 YLÖJÄRVEN KAUPUNKI KUNNALLISTEKNINEN SUUNNITTELU		Piirt. T. Koivumäki	Pvm 12.11.2020	Työ nro 2020-23
		Suunn. Mirko Harjula		
		Tark.		Piir. nro 3.4
		Hyv.		